

MINILINE

PERFORMANCE LEVEL

UW-VALUE		1.5 W/m ² K*
AIR TRANSMISSION	NBN EN 12207	Classe 4
WATERTIGHTNESS	NBN EN 12208	Classe 8A
RESISTANCE TO WIND	NBN EN 12210	Classe A4
ACOUSTICAL INSULATION		up to 38dB (-1; -5)

* 5000mm x 2800mm / UG 0.8 W/m²K & PSI 0.036W/MK / profiel combinatie: MIN010 - MIN020

TECHNICAL FEATURES

- Galandage, duo-rail or tri-rail
- Vertical centre post of 20 mm
- Open angle of 90°
- Completely barrier-free
- Maximum vent weight : 500kg
- Maximum dimensions : 4000 mm high - 12 m2 surface area - glass thickness 36 mm

100% MADE IN BELGIUM



Aliplast develops aluminium profiles tailored to current housing needs. Everything happens under one roof: from drawing to extrusion, powder coating, insulation and transport to the Aliplast distributors. The distributors produce and install the finished windows in your building project.

25-YEAR COLOUR GUARANTEE



Aliplast gives a 25-year guarantee on 50 current colours. The Qualicoat Seaside quality label ensures that your paint colour is extra protected against aggressive environments (exhaust fumes, salty sea air, etc.). You enjoy a 15-year guarantee on all other colours. Peace of mind for the future.

DURABLE PRODUCT



Aluminium is a durable product because it has a long lifespan. Moreover, the material is fully recyclable and can therefore be completely reused without compromising on quality. Aliplast mainly uses recycled aluminium billets for architectural systems. This aluminium is "Green Metal". It has a positive impact on people and the environment.



MINILINE

Design in minimalisme

100%
MADE IN
BELGIUM

25
YEARS
COLOR
LOCKED



aliplast[®]
ALUMINIUM SYSTEMS

ALIPLAST PLC

WAASLANDLAAN 15 | B - 9160 LOKEREN | INFO@ALIPLAST.COM | WWW.ALIPLAST.COM

MINI-EN-202302

MINILINE

MINIMALIST SLIDING WINDOWS



The **MINILINE** is a minimalist sliding glass wall. All aluminium profiles are built into the ground, ceiling and wall. Remains: **only the vertical aluminium profile only 20 mm wide**. Thermally insulated.

Thanks to the fully integrated ultra-slim profiles, transparency is maximised. This system is **completely barrier-free** and regulates drainage with a sloping pedestal profile connected to a drainage channel on the outside of the sliding window.

Very large sliding glass sashes are possible with a maximum weight of up to 500kg. The miniline is available in galandage, duo or tri-rail versions.

The **open corner solution** provides a spatial connection between inside and outside. An uninterrupted view to enjoy.